



IMPACT PROTECTION



CUT
EN388



4342



Tested for harmful substances according to Oeko-Tex® Standard 100
9-EO 096266 TESTEX

ATTRIBUTES:

LINER

13g Salt and Pepper HDPE
A3 Basetek Liner

COATING

Black HCT® MicroFoam
Nitrile Palm Coating

FEATURES:

- Back of Hand TPV Protection
- Padded Gel Palm

APPLICATIONS:

- Construction
- Oil and Gas
- Mining

Armor Guys reference number : 02-030

CATEGORY:

Basetek

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:



SPECIFICATIONS

LINER MATERIALS	13g Salt and Pepper HDPE A5 Basetek Liner
COATING MATERIALS	Black HCT® MicroFoam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	XS-XXL

PACKAGING

CASE SIZE	XS	S	M	L	XL	XXL
PER CARTON	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
ORIGIN	PRC					

PERFORMANCE LEVEL

EN388: 4342	EN Level 3 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5