



ATTRIBUTES:

LINER
13g Taeki5® A4 Liner

COATING
Double Dipped HCT® Nitrile

FEATURES:

- Optimal Cut Protection Combined With Liquid Resistance

APPLICATIONS:

- Oil and Gas
- Mining
- Machining

Armor Guys reference number : 05-005

CATEGORY:

Chemiflex

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:



SPECIFICATIONS

LINER MATERIALS	13g Taeki5® A4 Liner
COATING MATERIALS	Double Dipped HCT® Nitrile
SIZES	M-XXL

PACKAGING				
CASE SIZE	M	L	XL	XXL
PER CARTON	10DZ	10DZ	10DZ	10DZ
CASE WEIGHT	48.50/lbs	50.70/lbs	52.90/lbs	59.50/lbs
ORIGIN	PRC			

PERFORMANCE LEVEL

EN388: 4X44C							
ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	X