




**ARMOR GUYS**  
• PROTECTED •



**01-019 SPECIFICATION SHEET**



**ATTRIBUTES:**

**LINER**

18" Taeki5® A4 Hi Vis Yellow Sleeve

**FEATURES:**

- Single Ply
- Light Heat Resistance
- Moisture Wicking
- Lint Free

**APPLICATIONS:**

- Automotive Assembly
- Light Manufacturing
- Sheet Metal Handling
- Construction
- Recycling

Armor Guys Reference Number: 01-019

**CATEGORY:**

Taeki5®

**SPECIFICATIONS**

LINER MATERIALS	Hi-Vis Yellow Taeki5® A4 Fiber
WRIST DESIGN	Continuous Knit
SIZES	One Size
PACKAGING	120 Each
LENGTH	18 inch
CASE WEIGHT	20.70/lbs.
ORIGIN	PRC

**PERFORMANCE LEVEL**

EN388: 444XD	EN Level 4 Cut Resistance						
ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	



Performance	TAEKI5®	HDPE* UHMWPE**	META-ARAMID PARA-ARAMID
Abrasion Resistance	++	++	-
Cut Resistance	++	+	-
Heat Contact Resistance	+	x	+
Washing	++	+	-
UV Resistance	++	++	x
Lint Free	++	++	x
Any Color Available	++	-	-
Comfort	++	++	+
Variety of Coating Available Including Nitrile, PVC and Latex	++	-	+
Quality/Price Ratio	++	-	+
<b>Total Performance</b>	<b>+29</b>	<b>+19</b>	<b>+12</b>

\*HDPE=High Density Polyethylene  
 \*\*UHMWPE=Ultra High Molecular Weight Polyethylene  
 Testing Method based on both CE and ANSI standard

3	++	HIGH	1	-	LOW
2	+	MEDIUM	0	x	NO

**CARE INSTRUCTIONS:**

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)