




# ARMOR GUYS

• PROTECTED •



01-020

SPECIFICATION SHEET



### ATTRIBUTES:

#### LINER

10g Yellow Taeki5®  
A4 Liner

#### COATING

Sewn on Leather Palm

### FEATURES:

- Moderate Heat Resistance

### APPLICATIONS:

- Steel Processing
- Sheet Metal Handling
- Metal Stamping

Armor Guys Reference Number: 01-006

### CATEGORY:

Taeki5®

### SPECIFICATIONS

<b>LINER MATERIALS</b>	10g Yellow Taeki5® A4 Liner
<b>COATING MATERIALS</b>	Gray Sewn on Leather
<b>WRIST DESIGN</b>	Continuous Knit
<b>SIZES</b>	S-XXL

<b>PACKAGING</b>					
<b>CASE SIZE</b>	S	M	L	XL	XXL
<b>PER CARTON</b>	5DZ	5DZ	5DZ	5DZ	5DZ
<b>CASE WEIGHT</b>	29.07/lbs	32.16/lbs	33.48/lbs	35.24/lbs	37.24/lbs
<b>CUFF COLOR</b>	Red	Yellow	Brown	Black	Blue
<b>ORIGIN</b>	PRC				

### PERFORMANCE LEVEL

<b>EN388: 4X44D</b>							
<b>ABRASION</b>	0	1	2	3	4	5	X
<b>CUT</b>	0	1	2	3	4	5	X
<b>TEAR</b>	0	1	2	3	4	5	X
<b>PUNCTURE</b>	0	1	2	3	4	5	X
<b>CUT TDM TEST</b>	A	B	C	D	E	F	

### TECHNOLOGIES:



Performance	TAEKI5®	HDPE* UHMWPE**	META-ARAMID PARA-ARAMID
Abrasion Resistance	++	++	-
Cut Resistance	++	+	-
Heat Contact Resistance	+	x	+
Washing	++	+	-
UV Resistance	++	++	x
Lint Free	++	++	x
Any Color Available	++	-	-
Comfort	++	++	+
Variety of Coating Available Including Nitrile, PVC and Latex	++	-	+
Quality/Price Ratio	++	-	+
<b>Total Performance</b>	+29	+19	+12

\*HDPE=High Density Polyethylene

\*\*UHMWPE=Ultra High Molecular Weight Polyethylene

3 ++ HIGH 1 - LOW

Testing Method based on both CE and ANSI standard

2 + MEDIUM 0 x NO

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)