



ARMOR GUYS


• PROTECTED •



01-031 SPECIFICATION SHEET



THUMB CROTCH REINFORCEMENT



ATTRIBUTES:

LINER

13g Lime Green Taeki5®
A3 Liner

COATING

Gray Polyurethane
Palm Coating

FEATURES:

- Light Heat Resistance
- Moisture Wicking
- Lint Free

APPLICATIONS:

- Light Manufacturing
- Sheet Metal Handling
- Metal Stamping
- Construction

Armor Guys Reference Number: 01-031

CATEGORY:

Taeki5®

SPECIFICATIONS

LINER MATERIALS	13g Lime Green Taeki5® A3 Liner
COATING MATERIALS	Gray Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	XS-XXXL

PACKAGING							
CASE SIZE	XS	S	M	L	XL	XXL	XXXL
PER CARTON	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue	Gray
ORIGIN	PRC						

PERFORMANCE LEVEL

EN388: 4342C	EN Level 3 Cut Resistance						
ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

TECHNOLOGIES:



⚠ This product can expose you to N,N-Dimethylformamide-which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

Performance	TAEKI5®	HDPE* UHMWPE**	META-ARAMID PARA-ARAMID
Abrasion Resistance	++	++	-
Cut Resistance	++	+	-
Heat Contact Resistance	+	x	+
Washing	++	+	-
UV Resistance	++	++	x
Lint Free	++	++	x
Any Color Available	++	-	-
Comfort	++	++	+
Variety of Coating Available Including Nitrile, PVC and Latex	++	-	+
Quality/Price Ratio	++	-	+
Total Performance	+29	+19	+12

*HDPE=High Density Polyethylene
**UHMWPE=Ultra High Molecular Weight Polyethylene

Testing Method based on both CE and ANSI standard

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)