



### ATTRIBUTES:

#### LINER

13g Light Gray HDPE  
A2 Basetek Liner

#### COATING

Black Polyurethane  
Palm Coating

### FEATURES:

- Positive Grip in Dry and Light Oil Environments

### APPLICATIONS:

- Appliance Manufacturing
- Automotive Manufacturing
- Construction
- Sheet Metal Handling
- Small Parts Assembly

**Armor Guys reference number :** 02-021

### CATEGORY:

Basetek

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

### TECHNOLOGIES:



**⚠** This product can expose you to N,N-Dimethylformamide- which is known to the State of California to cause cancer. For more information go to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov)

### SPECIFICATIONS

LINER MATERIALS	13g Light Gray HDPE A2 Basetek Liner
COATING MATERIALS	Black Polyurethane
WRIST DESIGN	Continuous Knit
SIZES	XXS-XXXL

PACKAGING								
CASE SIZE	XXS	XS	S	M	L	XL	XXL	XXXL
PER CARTON	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ
CASE WEIGHT	10.23/lbs	11.23/lbs	11.72/lbs	12.05/lbs	14.98/lbs	15.42/lbs	16.08/lbs	19.08/lbs
CUFF COLOR	Pink	Purple	Red	Yellow	Brown	Black	Blue	Gray
ORIGIN	PRC							

### PERFORMANCE LEVEL

EN388: 3221B	EN Level 2 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F