



ARMOR GUYS
• PROTECTED •

EXTRAFLEX
OLYMPUS™

04-300 SPECIFICATION SHEET

ATTRIBUTES:

LINER

13g Light Blue Engineered A3 Liner

COATING

Black HCT® MicroFoam Nitrile Palm Coating

FEATURES:

- Reinforced Thumb Crotch
- MicroFoam Coating Ensures Excellent Oil Grip

APPLICATIONS:

- Automotive Manufacturing
- Light Manufacturing
- Sheet Metal Handling
- Metal Stamping
- Construction

Armor Guys reference number : 04-300

CATEGORY:

Extraflex

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F)

TECHNOLOGIES:



THUMB CROTCH REINFORCEMENT



EN388



4442C



Tested for harmful substances according to Oeko-Tex® Standard 100 SH100 090266 TESTEX

SPECIFICATIONS

LINER MATERIALS	13g Light Blue Engineered A3 Liner
COATING MATERIALS	Black HCT® MicroFoam Nitrile
WRIST DESIGN	Continuous Knit
SIZES	XXS-XXXL

PACKAGING

CASE SIZE	XXS	XS	S	M	L	XL	XXL	XXXL
PER CARTON	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ
CASE WEIGHT	13.76/lbs	14.76/lbs	15.20/lbs	15.86/lbs	18.94/lbs	20.48/lbs	22.48/lbs	25.48/lbs
CUFF COLOR	Pink	Purple	Red	Yellow	Brown	Black	Blue	Gray
ORIGIN	PRC							

PERFORMANCE LEVEL

EN388: 4442C	EN Level 4 Cut Resistance					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F