

EXTRAFLEX®

04-312

SPECIFICATION SHEET



CUT
EN388



4443D
EN511



X2X



SPECIFICATIONS:

- **Liner Materials:** 13g Light Blue Engineered A4 Liner
- **Coating Materials:** Black HCT® MicroFoam Nitrile
- **Wrist Design:** Continuous Knit
- **Origin:** PRC
- **Sizes:** S-XXXL

Armor Guys Reference Number: 04-312

PACKAGING:

GLOVE SIZE	S	M	L	XL	XXL	XXXL
CUFF COLOR	Red	Yellow	Brown	Black	Blue	Gray
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

PERFORMANCE LEVEL:

EN388: 4443D – EN Level 4 Cut Resistance

ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F

ATTRIBUTES:

- 13g Light Blue Engineered A4 Liner With 7g Poly-Acrylic Lining
- Black HCT® MicroFoam Nitrile Knuckle Coating

FEATURES:

- Knuckle Coating for Added Back of Hand Liquid Resistance
- Excellent Abrasion Resistance & Wet Grip
- Breathable Coating for Superior Comfort

APPLICATIONS:

- Construction
- Cold Storage
- Outdoor Winter Work
- Landscaping

CATEGORY:

- **Extraflex®**

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:



Hybrid Coating Technology

ARMOR GUYS

• PROTECTED •