

# EXTRAFLEX® PLUS+

## 14-300 SPECIFICATION SHEET



TOUCH  
SCREEN



CUT



ABR



PUN

EN388



4X42C



### SPECIFICATIONS:

- **Liner Materials:** 18g, Blue Extraflex® Plus A3 Liner
- **Coating Materials:** Black HCT® MicroFoam Nitrile
- **Wrist Design:** Continuous Knit
- **Origin:** PRC
- **Sizes:** XS-XXL

**Armor Guys Reference Number:** 14-300

### PACKAGING:

<b>GLOVE SIZE</b>	XS	S	M	L	XL	XXL
<b>CUFF COLOR</b>	Purple	Red	Yellow	Brown	Black	Blue
<b>PER CASE</b>	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

### PERFORMANCE LEVEL:

EN388: 4X42C

<b>ABRASION</b>	0	1	2	3	4	5	X
<b>CUT</b>	0	1	2	3	4	5	X
<b>TEAR</b>	0	1	2	3	4	5	X
<b>PUNCTURE</b>	0	1	2	3	4	5	X
<b>CUT TDM TEST</b>	A	B	C	D	E	F	

### ATTRIBUTES:

- 18g, Blue Extraflex® Plus A3 Liner
- Black HCT® MicroFoam Nitrile Palm Coating

### FEATURES:

- Reinforced Thumb Crotch
- Touchscreen Compatible
- MicroFoam Coating Ensures Excellent Oil Grip

### APPLICATIONS:

- Automotive Manufacturing
- Light Manufacturing
- Sheet Metal Handling
- Metal Stamping
- Construction

### CATEGORY:

- Extraflex® Plus

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:



**ARMOR GUYS**  
• PROTECTED •