

# EXTRAFLEX®

## 04-550

## SPECIFICATION SHEET



### ATTRIBUTES:

- 18g Dark Gray Engineered A5 Liner
- Black HCT® Nano-Foam Nitrile Palm Coating

### FEATURES:

- Reinforced Thumb Crotch
- Nano-Foam Coating Provides Unparalleled Dexterity & Tactile Sensitivity
- Excellent Dry Grip

### APPLICATIONS:

- Automotive Manufacturing
- Sheet Metal Handling
- Construction
- Metal Stamping
- Glass Handling

### CATEGORY:

- Extraflex®

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:



### SPECIFICATIONS:

- **Liner Materials:** 18g Dark Gray Engineered A5 Liner
- **Coating Materials:** Black HCT® Nano-Foam Nitrile
- **Wrist Design:** Continuous Knit
- **Origin:** PRC
- **Sizes:** XS-XXL

**Armor Guys Reference Number:** 04-550

### PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	XXL
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	10DZ	10DZ	10DZ	10DZ	10DZ	10DZ
CASE WEIGHT	13.22/lbs	13.66/lbs	14.10/lbs	15.42/lbs	16.08/lbs	17.18/lbs

### PERFORMANCE LEVEL:

**EN388: 4342E** – EN Level 3 Cut Resistance

ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F

# ARMOR GUYS

• PROTECTED •