



KYORENE®
THE GRAPHENE FIBER

00-320

SPECIFICATION SHEET



TOUCH SCREEN



CUT



ABR



PUN

EN388



4442B



UPF 100

Oeko-Tex® Standard 100

ATTRIBUTES:

- 13g Gray Kyorene® Graphene A3 Liner
- Black Polyurethane Palm Coating

FEATURES:

- Reinforced Thumb Crotch for Extended Wear
- Bacteriostatic Kills Harmful Bacteria
- Thermal Regulating to Keep the Hands Comfortable
- Odor Neutralizing to Keep the Gloves Smelling Fresh

APPLICATIONS:

- Automotive Manufacturing
- Appliance Manufacturing
- Metal Stamping
- Sheet Metal Handling
- Construction

CATEGORY:

- Kyorene®

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:



KYORENE®
THE GRAPHENE FIBER

⚠ This product can expose you to N,N-Dimethylformamide which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

SPECIFICATIONS:

- **Liner Materials:** 13g Gray Kyorene® Graphene A3 Liner
- **Coating Materials:** Black Polyurethane
- **Wrist Design:** Continuous Knit
- **Origin:** PRC
- **Sizes:** XS-XXL

Armor Guys Reference Number: 00-320

PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	XXL
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

PERFORMANCE LEVEL:

EN388: 4442B– EN Level 4 Cut Resistance

ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT TDM TEST	A	B	C	D	E	F



VERIFIED GRAPHENE®
PRODUCER
THE GRAPHENE COUNCIL

ARMOR GUYS
• PROTECTED •