

# EXTRAFLEX® PLUS+

## 14-300 SPECIFICATION SHEET



TOUCH  
SCREEN



CUT



ABR



PUN  
EN388



4X42C



Oeko-Tex®  
Standard 100

### ATTRIBUTES:

- 18g Blue Extraflex® Plus A3 Liner
- Black HCT® MicroFoam Nitrile Palm Coating

### FEATURES:

- Reinforced Thumb Crotch
- Touchscreen Compatible
- MicroFoam Coating Ensures Excellent Oil Grip

### APPLICATIONS:

- Automotive Manufacturing
- Light Manufacturing
- Sheet Metal Handling
- Metal Stamping
- Construction

### CATEGORY:

- Extraflex® Plus

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:



Hybrid Coating Technology

### SPECIFICATIONS:

- **Liner Materials:** 18g Blue Extraflex® Plus A3 Liner
- **Coating Materials:** Black HCT® MicroFoam Nitrile
- **Wrist Design:** Continuous Knit
- **Origin:** PRC
- **Sizes:** XS-XXL

Armor Guys Reference Number: 14-300

### PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	XXL
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

### PERFORMANCE LEVEL:

EN388: 4X42C

ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

