

EXTRAFLEX® PLUS+

14-620 SPECIFICATION SHEET



TOUCH
SCREEN



CUT



ABR



PUN

EN388



4X44F



Oeko-Tex®
Standard 100

SPECIFICATIONS:

- **Liner Materials:** 18g Red Extraflex® Plus A6 Liner
- **Coating Materials:** Black Polyurethane
- **Wrist Design:** Continuous Knit
- **Origin:** PRC
- **Sizes:** XS-XXL

Armor Guys Reference Number: 14-620

PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	XXL
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

PERFORMANCE LEVEL:

EN388: 4X44F – EN Level 4 Cut Resistance

ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

⚠ This product can expose you to N,N-Dimethylformamide-which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov

ATTRIBUTES:

- 18g Red Extraflex® Plus A6 Liner
- Black Polyurethane Palm Coating

FEATURES:

- Reinforced Thumb Crotch for Extended Wear
- Touchscreen Compatible

APPLICATIONS:

- Metal Fabrication
- Metal Stamping
- Steel Processing
- Steel Handling
- Recycling

CATEGORY:

- Extraflex® Plus

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:

EXTRAFLEX®
PLUS+

