



ANSI/ISEA 105



EN388



3X42F



UPF 100



STANDARD 100
SHEDDING TEST



SPECIFICATIONS:

- **Liner Materials:** 21g Gray Kyorene[®] Pro Graphene A9 Liner
- **Coating Materials:** Soft Gray Polyurethane
- **Wrist Design:** Continuous knit
- **Origin:** PRC
- **Sizes:** XS-2X

Armor Guys Reference Number: 21-893

PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	2X
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ
CASE WEIGHT	6.61 lbs	7.05 lbs	7.50 lbs	7.72 lbs	8.16 lbs	8.38 lbs

PERFORMANCE LEVEL:

EN388: 3X42F

ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

ATTRIBUTES:

- 21g Gray Kyorene[®] Pro Graphene A9 Liner
- Soft Gray Polyurethane Palm Coating

FEATURES:

- Silicone free
- Touchscreen compatible
- Reinforced thumb crotch for extended wear
- Ergonomically shaped for superior fit

GRAPHENE BENEFITS:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- UV protection against UV-A and UV-B rays

APPLICATIONS:

- Automotive manufacturing
- Metal fabrication
- Steel processing
- Construction

CATEGORY:

- Kyorene[®] Pro

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:

KYORENE[®]
PRO GRAPHENE

HCT
Hybrid Coating Technology

