



### ANSI/ISEA 105



EN388



4X22B

EN511



X11



UPF  
100

Oeko-Tex<sup>®</sup>  
Standard 100



### SPECIFICATIONS:

- **Liner Materials:** 15g Gray Kyorene<sup>®</sup> Pro Graphene A4 Waterproof Liner, 7g Poly-Acrylic Lining
- **Coating Materials:** Black HCT<sup>®</sup> MicroFoam Nitrile
- **Wrist Design:** Continuous knit
- **Origin:** PRC
- **Sizes:** XS-2X

Armor Guys Reference Number: 00-819WP

### PACKAGING:

| GLOVE SIZE  | XS       | S        | M        | L        | XL       | 2X       |
|-------------|----------|----------|----------|----------|----------|----------|
| CUFF COLOR  | Purple   | Red      | Yellow   | Brown    | Black    | Blue     |
| PER CASE    | 6DZ      | 6DZ      | 6DZ      | 6DZ      | 6DZ      | 6DZ      |
| CASE WEIGHT | 6.61 lbs | 7.05 lbs | 7.50 lbs | 7.72 lbs | 9.04 lbs | 9.70 lbs |

### PERFORMANCE LEVEL:

#### EN388: 4X22B

| ABRASION     | 0 | 1 | 2 | 3 | 4 | 5 | X |
|--------------|---|---|---|---|---|---|---|
| CUT          | 0 | 1 | 2 | 3 | 4 | 5 | X |
| TEAR         | 0 | 1 | 2 | 3 | 4 | 5 | X |
| PUNCTURE     | 0 | 1 | 2 | 3 | 4 | 5 | X |
| CUT TDM TEST | A | B | C | D | E | F |   |

### ATTRIBUTES:

- 15g Gray Kyorene<sup>®</sup> Pro Graphene A2 Waterproof Liner With 7g Poly-Acrylic Lining
- Black HCT<sup>®</sup> MicroFoam Nitrile Palm Coating

### FEATURES:

- Silicone free
- Touchscreen compatible
- Hi vis reinforced thumb crotch for extended wear
- Ergonomically shaped for superior fit

### GRAPHENE BENEFITS:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- UV protection against UV-A and UV-B rays

### APPLICATIONS:

- Cold storage
- Fishing
- Outdoor winter work
- Landscaping

### CATEGORY:

- Kyorene<sup>®</sup> Pro

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:

KYORENE<sup>®</sup>  
PRO GRAPHENE

HCT  
Hybrid Coating Technology

