



TOUCH
SCREEN



ANSI/ISEA 105



EN388



4X42D



UPF
100



STANDARD
100
SHEDDING
TESTED



SPECIFICATIONS:

- **Liner Materials:** 24g Gray Kyorene Pro[®] Max Graphene A4 Liner
- **Coating Materials:** Soft Black HCT[®] MicroFoam Nitrile
- **Wrist Design:** Continuous knit
- **Origin:** PRC
- **Sizes:** XS-2X

Armor Guys Reference Number: 24-840

PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	2X
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ
CASE WEIGHT	8.38 lbs	8.93 lbs	9.46 lbs	10.01 lbs	10.78 lbs	11.77 lbs

PERFORMANCE LEVEL:

EN388: 4X42D

ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

ATTRIBUTES:

- 24g Gray Kyorene Pro[®] Max Graphene A4 Liner
- Soft Black HCT[®] MicroFoam Nitrile Palm Coating

FEATURES:

- Silicone free
- Touchscreen compatible
- Reinforced thumb crotch for extended wear
- Ergonomically shaped for superior fit

GRAPHENE BENEFITS:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- UV protection against UV-A and UV-B rays

APPLICATIONS:

- Data centers
- Electrical work
- Small parts handling
- Automotive manufacturing
- Sheet metal handling
- Metal stamping
- Steel processing
- Construction

CATEGORY:

- Kyorene Pro[®] Max

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:



VERIFIED GRAPHENE
PRODUCER
THE GRAPHENE COUNCIL



ARMOR GUYS

KYORENE[®]
PRO GRAPHENE

HCT
Hybrid Coating Technology