



ANSI/ISEA 105



EN388



3X42D



### SPECIFICATIONS:

- **Liner Materials:** 24g Gray Kyorene Pro<sup>®</sup> Max Graphene A4 Liner
- **Coating Materials:** Soft Gray Polyurethane
- **Wrist Design:** Continuous knit
- **Origin:** PRC
- **Sizes:** XS-2X

Armor Guys Reference Number: 24-843

### PACKAGING:

| GLOVE SIZE  | XS       | S        | M        | L        | XL       | 2X       |
|-------------|----------|----------|----------|----------|----------|----------|
| CUFF COLOR  | Purple   | Red      | Yellow   | Brown    | Black    | Blue     |
| PER CASE    | 6DZ      | 6DZ      | 6DZ      | 6DZ      | 6DZ      | 6DZ      |
| CASE WEIGHT | 6.39 lbs | 6.83 lbs | 7.28 lbs | 7.72 lbs | 7.94 lbs | 8.38 lbs |

### PERFORMANCE LEVEL:

EN388: 3X42D

| ABRASION     | 0 | 1 | 2 | 3 | 4 | 5 | X |
|--------------|---|---|---|---|---|---|---|
| CUT          | 0 | 1 | 2 | 3 | 4 | 5 | X |
| TEAR         | 0 | 1 | 2 | 3 | 4 | 5 | X |
| PUNCTURE     | 0 | 1 | 2 | 3 | 4 | 5 | X |
| CUT TDM TEST | A | B | C | D | E | F |   |

### ATTRIBUTES:

- 24g Gray Kyorene Pro<sup>®</sup> Max Graphene A4 Liner
- Soft Gray Polyurethane Palm Coating

### FEATURES:

- Silicone free
- Touchscreen compatible
- Reinforced thumb crotch for extended wear
- Ergonomically shaped for superior fit

### GRAPHENE BENEFITS:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- UV protection against UV-A and UV-B rays

### APPLICATIONS:

- Data centers
- Electrical work
- Small parts handling
- Automotive manufacturing
- Sheet metal handling
- Metal stamping
- Steel processing
- Construction

### CATEGORY:

- Kyorene Pro<sup>®</sup> Max

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:

KYORENE<sup>®</sup>  
PRO GRAPHENE

