



ANSI/ISEA 105



EN388



3X42D



UPF 100



STANDARD 100
SHOUD 10000
TESTEX



SPECIFICATIONS:

- **Liner Materials:** 24g Gray Kyorene Pro[®] Max Graphene A4 Liner
- **Coating Materials:** Soft Gray Polyurethane
- **Wrist Design:** Continuous knit
- **Origin:** PRC
- **Sizes:** XS-2X

Armor Guys Reference Number: 24-843

PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	2X
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ
CASE WEIGHT	6.39 lbs	6.83 lbs	7.28 lbs	7.72 lbs	7.94 lbs	8.38 lbs

PERFORMANCE LEVEL:

EN388: 3X42D

	0	1	2	3	4	5	X
ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

ATTRIBUTES:

- 24g Gray Kyorene Pro[®] Max Graphene A4 Liner
- Soft Gray Polyurethane Palm Coating

FEATURES:

- Silicone free
- Touchscreen compatible
- Reinforced thumb crotch for extended wear
- Ergonomically shaped for superior fit

GRAPHENE BENEFITS:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- UV protection against UV-A and UV-B rays

APPLICATIONS:

- Data centers
- Electrical work
- Small parts handling
- Automotive manufacturing
- Sheet metal handling
- Metal stamping
- Steel processing
- Construction

CATEGORY:

- Kyorene Pro[®] Max

CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

TECHNOLOGIES:

KYORENE PRO[®] MAX



This product can expose you to N,N-Dimethylformamide which is known to the State of California to cause cancer. For more information go to www.P65warnings.ca.gov