



TOUCH  
SCREEN



### ANSI/ISEA 105



EN388



4X42F

ANSI/ISEA 138



### SPECIFICATIONS:

- **Liner Materials:** 21g Gray Kyorene Pro<sup>®</sup> Graphene A9 Liner
- **Coating Materials:** Soft Black HCT<sup>®</sup> MicroFoam Nitrile
- **Wrist Design:** Continuous knit
- **Origin:** PRC
- **Sizes:** XS-2X

Armor Guys Reference Number: 21-897

### PACKAGING:

GLOVE SIZE	XS	S	M	L	XL	2X
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ
CASE WEIGHT	21.65 lbs	22.00 lbs	25.42 lbs	26.81 lbs	28.86 lbs	33.75 lbs

### PERFORMANCE LEVEL:

#### EN388: 4X42F

ABRASION	0	1	2	3	4	5	X
CUT	0	1	2	3	4	5	X
TEAR	0	1	2	3	4	5	X
PUNCTURE	0	1	2	3	4	5	X
CUT TDM TEST	A	B	C	D	E	F	

### ATTRIBUTES:

- 21g Gray Kyorene Pro<sup>®</sup> Graphene A9 Liner
- Soft Black HCT<sup>®</sup> MicroFoam Nitrile Palm Coating

### FEATURES:

- Silicone free
- Touchscreen compatible
- Back of hand TPV protection
- Reinforced thumb crotch for extended wear
- Ergonomically shaped for superior fit

### GRAPHENE BENEFITS:

- No stainless steel or fiberglass
- Bacteriostatic kills harmful bacteria
- Thermal regulating to keep the hands comfortable
- Odor neutralizing to keep the gloves smelling fresh
- UV protection against UV-A and UV-B rays

### APPLICATIONS:

- Oil & gas
- Mining
- Construction

### CATEGORY:

- Kyorene Pro<sup>®</sup>

### CARE INSTRUCTIONS:

Recommended washing temperature is between 40°C and 60°C (104 - 140°F) with mild detergent.

The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F).

### TECHNOLOGIES:

KYORENE<sup>®</sup>  
PRO GRAPHENE

HCT  
Hybrid Coating Technology

